

Power Secure LBR20 LED Lamp



Solais LED BR20 Lamp Replacement

Product Description: The Solais passive LED BR20 lamp replacement offers a unique solution for traditional lighting sources – providing the incandescent performance, light output and aesthetics with our recessed OPTICS2 patent-pending technology.

Performance Summary: Fully dimmable | Halogen PAR form factor (ANSI compliant) | Lightest LED lamps on the market | Certified to UL Standard 1993 | RoHS-compliant | Contain no lead or mercury | Damp location rating

Application: Designed for use in track and recessed fixtures (including IC rated housing)

Voltage: 120v Standard

CCT: 2700K, 3000K, 3500K*, 4000K*

Dimmable: Yes - Visit solais.com/dimming.php for compatibility list

Life: 50,000 Hours (L70)

Power Factor: .92


Base Type: E26, GU24*

Weight (oz.):



Product Code	Power (Watts)	Beam Angle	CCT (K)	Lumen Output	CBCP (cd)	CRI
LBR20/FL/30K	7	FL	3000	475	N/A	85
LBR20/FL/27K	7	FL	2700	450	N/A	85

Lamp Images



Ordering Information

Example: LBR20/40/30K

LBR20	/	FL	/
Form Factor (R20) LBR20		Beam Spread FL	CCT 27K 30K 35K* 40K*

* Made to Order

Beam Angles



Flood

Color Temperature

2700K	3000K	3500K*	4000K*

Housing Colors

Silver

Power Secure LBR20 LED Lamp



OPTICS2 involves a recessed primary optic and surface secondary optic that allows Solais LRP lamps to duplicate the exact performance and aesthetics of incandescents.



Thermal Throttle – In the event that Solais LEDs become overheated, they will dim themselves to protect your technology investments.

LIMITED WARRANTY: Turolight warrants that this lamp will operate for a period of five (5) years from the date of purchase when used in accordance with package and lamp directions. If this lamp does not last for three years, return this product to the place of purchase or visit turolight.com for warranty replacement procedures. You must include the original receipt/proof of purchase. Turolight will repair or replace your lamp. This limited warranty may not cover lamps subject to misuse, electrical current fluctuation, accident, neglect, or acts of God. THIS REPLACEMENT IS THE SOLE WARRANTY OBLIGATION OF TUROLIGHT AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE EXCLUDED. Exclusion of incidental or consequential damages is not allowed by some provinces, so the above limitation or exclusion may not apply to you. Please visit turolight.com and contact us using the form supplied with any questions. **WARNING:** Not for use in fully enclosed luminaires. **Caution:** Risk of electric shock. Use in an indoor, dry location only. This device is not intended for use with emergency exit fixtures or emergency exit lights. May not be compatible with all dimmers, please contact Turolight.com for up-to-date dimmer compatibility information. **NOTES:** This product may cause interference with other devices. If interference occurs, change the location of the products involved.