



Key Features

- Square welded aluminum ballast housing with powder coated finish for corrosion resistance
- UV resistant PC lens
- Options for both ceiling or pipe mounting

Electronic Features




- Globe or round tubular induction lamp with high lighting efficiency and life span of 100,000hours
- Stable lumen output and high lumen maintenance
- CRI higher than 80, and IP rating IP43 (control gear)
- High power factor (>0.95), flickering free operation with low ballast loss and constant output

Applications

- Garages
- Gas stations
- Parking lots
- Warehouses

Order Code	Model Number	Description	Lamp	Volts (V)	IP	Whole Package L xW xH (mm)	Lens	G.W. (kg)	Initial Lumens	UL cUL	CSA
3885502	ID-CPB-SB-A35	35W Ind.Garage,SB,5000K&Blst	A35L	120-277	43	400x400x335	PC	5.70	2450	Yes	-
3885511	ID-CPB-SB-A55	55W Ind.Garage,SB,5000K&Blst	A55L	120-277	43	400x400x335	PC	5.70	4125	Yes	-
3886108	ID-CPB-SB-C40	40W Ind.Garage,SB,5000K&Blst	C40L	120-277	43	400x400x335	PC	5.70	2800	Yes	-
3886109	ID-CPB-SB-C70	70W Ind.Garage,SB,5000K&Blst	C70L	120-277	43	400x400x335	PC	5.70	4900	Yes	-
3886110	ID-CPB-SB-C80	80W Ind.Garage,SB,5000K&Blst	C80L	120-277	43	400x400x335	PC	5.70	6000	Yes	-

*CCT(K) 5000K, Ambient Temp: -20 ~ +40, Ceiling Installation, Average Life 100,000 hours.



cd/klm η=76%
 — C0-C180 ID-CPB-SB-A55
 — C90-C270

Distributed by: