



Physical Features

- Energy Star listed
- Airtight Structure - to reduce heating and cooling cost
- Type IC Rated – approved for direct contact with insulation
- Isolated internal driver in junction box – fast and easy to install
- Slim design allows it to be installed in the plenum ceiling space
- Dimmable
- Damp location approved



Application

Residential / Institution Lighting
 School, Colleges, University and
 Hospitals, Supermarkets, Shops,
 Hotels, Conference Rooms, Office Lighting,
 Show Room, Corridor, Kitchen Room etc.

Electronic Features

- 1100 lumen stable lumen output
- 10W, 15W Replaces 50W, 75W halogen
- Long life span of 35,000 hours
- High CRI (80+)
- Working temperature ranges from -25° to +40°

Other information

- cETL ETL listed and ES listed
- 3-year limited warranty

| Order Code | Model Number | Description | ES | Watts | Volts | Hour Rating | Beam Angle | Init. Lum. | CCT (K) | CRI | Damp Loc | M.O.D. (inch) | CS Qty. |
|------------|----------------------|---|----|-------|-------|-------------|------------|------------|---------|-----|----------|---------------|---------|
| 1762774 | RGD-RK/4/SP/10W/30/D | RIGID 4" Slim Panel Down Light 10W 30K Dimmable | | 10 | 120 | 35,000 | 120° | 650 | 3000 | 80 | Y | 4.73 | 30 |
| 1762856 | RGD-RK/4/SP/10W/40/D | RIGID 4" Slim Panel Down Light 10W 40K Dimmable | | 10 | 120 | 35,000 | 120° | 650 | 4000 | 80 | Y | 4.73 | 30 |
| 1762775 | RGD-RK/6/SP/15W/30/D | RIGID 6" Slim Panel Down Light 15W 30K Dimmable | | 15 | 120 | 35,000 | 120° | 1100 | 3000 | 80 | Y | 7.09 | 30 |
| 1762857 | RGD-RK/6/SP/15W/40/D | RIGID 6" Slim Panel Down Light 15W 40K Dimmable | | 15 | 120 | 35,000 | 120° | 1100 | 4000 | 80 | Y | 7.09 | 30 |

Ambient Operating Temperature -25°C ~ +40°C

For the latest stock status please refer to your price list or send us an email at sales@turolight.com

How our Model No. Works:

Ordering Information

| | | | | | | |
|--------|-------------------|------------------|------------|------------|------------|----------|
| RGD | RK | 4 | SP | 10W | 30 | D |
| Family | Reflector Type | Size | Slim Panel | Wattage | CCT(K) | Dimmable |
| | RK - Retrofit Kit | 4 inch 6 inch | | 10W 15W | 30K 40K | |