

SPIRAL-LITE™

Compact Fluorescent Lamps

Features and Benefits

- 8,000-hour life
- ENERGY STAR® qualified
- Up to 80% energy savings compared to incandescent
- Same familiar shapes as incandescent
- Fits standard fixtures
- 1-year warranty

Spiral-Lite Covered CFLs Offer Attractive Savings in Familiar Shapes

Litetrionics Spiral-Lite™ Covered CFLs come in a variety of familiar shapes to combine the energy savings of compact fluorescent lamps with the attractive look and feel of an incandescent. Available in A19, G25, R30, R40, and PAR38, Spiral-Lite Covered CFLs provide up to 80% energy savings in a wide range of applications. These energy savings help lower utility bills and reduce greenhouse gas emissions.

Spiral-Lite Covered CFLs are ENERGY STAR® qualified and have an average life of 8,000 hours. This helps reduce replacement, labor, and maintenance costs. In addition to their familiar shapes, Spiral-Lite Covered CFLs have a either 2700K color temperature that provides the same warm lighting as incandescent lamps or a cool white, 4100K color. Replace inefficient incandescent lamps while maintaining the same attractive look with Spiral-Lite Covered CFLs.



G25

R30

R40

PAR38

A19

Applications

- General lighting
- Table lamps
- Floor lamps
- Ceiling fixtures
- Recessed cans
- Track lighting
- Theatres
- Bathrooms
- Vanities

 **TUROLIGHT®**
WWW.TUROLIGHT.COM

Toll Free: 1 (877) 736-0447 • Fax: (416) 736-4890
Email: info@turolight.com • Website: www.turolight.com

SPIRAL-LITE™ Compact Fluorescent Lamps

Covered



A19



G25



R30



R40



PAR38

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CRI	CORRELATED COLOR TEMP(K)	INITIAL LUMENS	MEAN LUMENS	M.O.L.**
A19	14 \$	MED	120	14W A19 27	L-14527A19-1	50	8,000	82	2700	850	725	4.88"
G25	14 \$	MED	120	14W G25 27	L-14527G25	24	8,000	82	2700	900	825	4.33"
R30	15 \$	MED	120	15W R30 27	L-15527R30-1	24	10,000	82	2700	750	675	5.47"
	15 \$	MED	120	15W R30 41	L-15541R30	24	10,000	82	4100	750	675	5.47"
R40	23 \$	MED	120	23W R40 27	L-23527R40	24	8,000	82	2700	1,300	1,175	6.34"
	23 \$	MED	120	23W R40 41	L-23541R40	24	10,000	82	4100	1,300	1,175	6.34"
PAR38	23 \$	MED	120	23W PAR38 27	L-23527P38	24	8,000	82	2700	1,300	1,175	6.34"
	23 \$	MED	120	23W PAR38 41	L-23541P38	24	10,000	82	4100	1,300	1,175	6.34"

SPECIFICATIONS

INPUT LINE FREQUENCY	50/60 HZ
RELIABLE OPERATING TEMP.	-5°F – 105°F
POWER FACTOR	> .50

CONVERSION CHART

CFL	=	INCANDESCENT
14-watt	=	60-watt
15-watt	=	65-watt
23-watt	=	120-watt

ENERGY STAR® Qualified

\$ Energy Savings

** Maximum Overall Length (in inches)

