

LITEPAR™

Halogen Lamps



PAR16

PAR30

PAR38

PAR30LN

PAR20

Features and Benefits

- 2,500 to 3,000-hour life
- Optimum focus and light distribution
- Special reflector and lens improve light distribution
- Superior lumen maintenance compared to incandescents

Applications

- Recessed cans
- Down lights
- Track lighting
- Open fixtures
- Office buildings
- Hospitals
- Restaurants
- Retail stores

A Brighter, Whiter Light with LITEPAR Halogen Lamps

LITEPAR™ halogen lamps are available in multiple sizes and can fit a variety of applications. Fitted with specially molded lenses, LITEPAR lamps offer optimum focus and consistent performance. Add in a 2,500 to 3,000-hour average life, and LITEPAR lamps become a clear choice for premium halogen lighting.

LITEPAR lamps offer a crisp light that enhances color and textures, making these lamps ideal for displaying merchandise. The bright light output makes LITEPAR lamps a great choice for any general lighting application, including recessed can and track lighting. LITEPAR lamps also have superior lumen maintenance when compared to incandescent lamps. For a bright light that lasts, LITEPAR is the clear choice.

 **TUROLIGHT®**
WWW.TUROLIGHT.COM

Toll Free: 1 (877) 736-0447 • Fax: (416) 736-4890
Email: info@turolight.com • Website: www.turolight.com

LITEPAR™ Halogen Lamps



PAR16



PAR20



PAR30



PAR30LN



PAR38

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	BEAM SPREAD	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	LUMENS	C.B.C.P.*	M.O.L.**
PAR16	60	MED	120-125	60 PAR16 NFL	NARROW FLOOD	L-3020	15	3,000	650	1,600	3.15"
	60	MED	130	60 PAR16 NFL	NARROW FLOOD	L-3030	15	2,500	650	1,600	3.15"
	75	MED	130	75 PAR16 NFL	NARROW FLOOD	L-3050	15	2,500	900	2,000	3.15"
PAR20	50	MED	120-125	50 PAR20 SP	SPOT	L-4426	15	3,000	525	5,000	3.15"
	50	MED	120-125	50 PAR20 FL	FLOOD	L-4425	15	3,000	525	1,600	3.15"
	50	MED	130	50 PAR20 FL	FLOOD	L-4428	15	2,500	520	1,600	3.15"
PAR30	50	MED	120-125	50 PAR30 SP	SPOT	L-4446	15	3,000	580	7,000	3.54"
	50	MED	120-125	50 PAR30 FL	FLOOD	L-4445	15	3,000	580	1,350	3.54"
	50	MED	130	50 PAR30 NFL	NARROW FLOOD	L-4444	15	2,500	580	2,400	3.54"
	50	MED	130	50 PAR30 FL	FLOOD	L-4447	15	2,500	580	1,350	3.54"
	75	MED	120-125	75 PAR30 FL	FLOOD	L-4455	15	3,000	1,050	2,100	3.54"
	75	MED	130	75 PAR30 SP	SPOT	L-4458	15	2,500	1,050	14,500	3.54"
	75	MED	130	75 PAR30 NFL	NARROW FLOOD	L-4460	15	2,500	1,050	4,000	3.54"
	75	MED	130	75 PAR30 FL	FLOOD	L-4457	15	2,500	1,050	2,300	3.54"
PAR30LN	50	MED	120-125	50 LN PAR30 FL	FLOOD	L-4445LN	15	3,000	550	1,200	4.68"
	50	MED	130	50 LN PAR30 NFL	NARROW FLOOD	L-4444LN	15	2,500	550	2,200	4.68"
	50	MED	130	50 LN PAR30 FL	FLOOD	L-4447LN	15	2,500	550	1,200	4.68"
	75	MED	120-125	75 LN PAR30 NFL	NARROW FLOOD	L-4459LN	15	3,000	1,000	3,600	4.68"
	75	MED	120-125	75 LN PAR30 FL	FLOOD	L-4455LN	15	3,000	1,000	2,300	4.68"
	75	MED	130	75 LN PAR30 SP	SPOT	L-4458LN	15	2,500	1,000	10,000	4.68"
	75	MED	130	75 LN PAR30 NFL	NARROW FLOOD	L-4460LN	15	2,500	1,000	3,600	4.68"
	75	MED	130	75 LN PAR30 FL	FLOOD	L-4457LN	15	2,500	1,000	2,300	4.68"
PAR38	45	MED	120-125	45 PAR38 FL	FLOOD	L-4091	15	3,000	520	2,000	5.19"
	45	MED	130	45 PAR38 FL	FLOOD	L-4094	15	2,500	520	2,000	5.19"
	60	MED	120-125	60 PAR38 FL	FLOOD	L-4510	15	3,000	800	3,500	5.19"
	60	MED	130	60 PAR38 FL	FLOOD	L-4514	15	2,500	800	3,500	5.19"
	75	MED	120-125	75 PAR38 FL	FLOOD	L-4088	15	3,000	1,100	4,800	5.19"
	75	MED	130	75 PAR38 SP	SPOT	L-4078	15	2,500	1,100	18,000	5.19"
	75	MED	130	75 PAR38 FL	FLOOD	L-4087	15	2,500	1,100	4,800	5.19"
	90	MED	120-125	90 PAR38 SP	SPOT	L-4080	15	3,000	1,280	27,500	5.19"
	90	MED	120-125	90 PAR38 FL	FLOOD	L-4081	15	3,000	1,280	5,000	5.19"
	90	MED	130	90 PAR38 FL	FLOOD	L-4084	15	2,500	1,280	5,000	5.19"

* Center Beam Candle Power

** Maximum Overall Length (in inches)

