

MICRO BRITE™

Decorative Cold Cathode Fluorescent Lamps



Features and Benefits

- 18,000 to 25,000-hour life
- Up to 85% energy savings compared to incandescent
- Dimmable (5-watt and 8-watt)
- Flashable (5-watt)
- Candelabra and medium bases
- Reduces replacement and maintenance costs
- Can be used indoors and outdoors
- 2-year warranty

Style and Substance with Micro-Brite Decorative Lamps

Litetrionics has applied its patented cold cathode fluorescent technology to a line of decorative Micro-Brite lamps. The Micro-Brite G16½ and G30 light bulbs are ideal for bathrooms, restaurants, hotels, hallways, and vanity mirror lighting. These lamps have an average rated life of 25,000 hours — twenty-six times longer than standard decorative incandescent lamps. They also offer up to 85% energy savings. With such high efficiency, Micro-Brite decorative lamps pay for themselves.

Micro-Brite C11 lamps are great for chandeliers, wall sconces, floor lighting, and table lighting. Available in candelabra and medium bases, the Micro-Brite C11 lamp is available with a bent tip for a more stylish design, and it is dimmable down to 5% of its light output. These lamps can provide efficient, long-lasting lighting for any occasion. Like all Micro-Brite lamps, these decorative lamps can be used indoors or outdoors in extreme temperatures. Get alluring lighting and attractive benefits with Micro-Brite decorative lamps.



G16.5

G30

C11

C11BT

Applications

- Marquees
- Sign applications
- Bathroom lighting
- Hallway lighting
- Chandelier lighting
- Hotels
- Wall sconces
- Floor and table lighting
- Building perimeter lighting

MICRO BRITE™ Cold Cathode Micro Compact Fluorescent Lamps



LAMP	WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CRI	CORRELATED COLOR TEMP(K)	INITIAL LUMENS	M.O.L.**
C11	5 \$	CAND LO	120	5W C11 CL PW	MB-540DP	30	25,000	82	2850	200	4.50"
	5 \$	CAND LO	120	5W C11 WH PW	MB-541DP	30	25,000	82	2850	200	4.50"
C11 BT	5 \$	MED LO	120	5W C11 CL PW BENT TIP	MB-543DP	30	25,000	82	2850	200	4.88"
	5 \$	MED LO	120	5W C11 WH PW BENT TIP	MB-545DP	30	25,000	82	2850	200	4.88"
	5 \$	CAND LO	120	5W C11 CL LW BENT TIP	MB-547DL	30	25,000	82	2250	200	5.00"
	5 \$	CAND LO	120	5W C11 CL PW BENT TIP	MB-547DP	30	25,000	82	2850	200	5.00"
	5 \$	CAND LO	120	5W C11 WH PW BENT TIP	MB-549DP	30	25,000	82	2850	200	5.00"
	5 \$	CAND LO	120	5W C11 WH LW BENT TIP	MB-549DL	30	25,000	82	2250	200	5.00"
G16.5	5 \$	CAND LO	120	5W G16.5 CL PW	MB-538DP	20	25,000	82	2850	200	3.54"
G30	8 \$	MED	120	8W G30 WH PW	MB-821DP	24	18,000	82	2850	325	5.77"

SPECIFICATIONS

INPUT LINE FREQUENCY	50/60 HZ
RELIABLE OPERATING TEMP.	5°F – 105°F
POWER FACTOR	> .90
TOTAL HARMONIC DISTORTION	< .30

CONVERSION CHART

CFL	=	INCANDESCENT
5-watt	=	30-watt
8-watt	=	45-watt

\$ Energy Savings

** Maximum Overall Length (in inches)

