

LED LAMP

PURE VISION




PV-PAR38, PV-PAR30, PV-PAR20



Features & Benefits

| | |
|--|------------------------------|
| Energy Star listed ,unique halogen looking lens design | Black housing available |
| Beam angle 40° & 25°, with wide color temperature options* | 25,000 hour average life |
| High CRI (80+), dimmable** | Enclosed fixture application |
| 16W replaces 120W halogen, 13W replaces 90W halogen, 12W replaces 75W halogen, 7W replaces 50W halogen | Wet location approved |

Dimensional drawing



Warranty & Cautions

| |
|---|
| 3-year limited warranty |
| Operating temperature range between -40°C and +45°C |
| UL/cUL listed, FCC compliant, RoHS compliant |

* PAR30LN, PAR20 5000K ES available. ** Check the dimmer compatibility list on our website www.turolight.com

Product Specification

| Ordering Code | ES | Model Number | Watts | Base | Voltage (V) | Hour Rating | Beam Angle | Initial Lumens(lm) | CCT(K) | CRI | C.B.C.P. (cd) | EFA ¹ | Wet LOC. | Damp LOC. | M.O.D. (inch) | M.O.L. (inch) | Case QTY. |
|---------------|----|----------------------------|-------|------|-------------|-------------|------------|--------------------|--------|-----|---------------|------------------|----------|-----------|---------------|---------------|-----------|
| PV-PAR38 | | | | | | | | | | | | | | | | | |
| 1733100 | Y | PV-PAR38/16W/27/WFL40/D/ES | 16 | E26 | 120 | 25,000 | 40° | 1400 | 2700 | 80 | 2270 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1733200 | Y | PV-PAR38/16W/30/WFL40/D/ES | 16 | E26 | 120 | 25,000 | 40° | 1400 | 3000 | 80 | 2270 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1733300 | Y | PV-PAR38/16W/35/WFL40/D/ES | 16 | E26 | 120 | 25,000 | 40° | 1400 | 3500 | 80 | 2270 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1733400 | Y | PV-PAR38/16W/40/WFL40/D/ES | 16 | E26 | 120 | 25,000 | 40° | 1400 | 4000 | 80 | 2270 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1733500 | Y | PV-PAR38/16W/50/WFL40/D/ES | 16 | E26 | 120 | 25,000 | 40° | 1400 | 5000 | 80 | 2270 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1733201 | Y | PV-PAR38/16W/30/FL25/D/ES | 16 | E26 | 120 | 25,000 | 25° | 1400 | 3000 | 80 | 3563 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1733401 | Y | PV-PAR38/16W/40/FL25/D/ES | 16 | E26 | 120 | 25,000 | 25° | 1400 | 4000 | 80 | 3563 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1732105 | Y | PV-PAR38/13W/27/WFL40/D/ES | 13 | E26 | 120 | 25,000 | 40° | 910 | 2700 | 80 | 1533 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1732205 | Y | PV-PAR38/13W/30/WFL40/D/ES | 13 | E26 | 120 | 25,000 | 40° | 910 | 3000 | 80 | 1533 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1732304 | Y | PV-PAR38/13W/35/WFL40/D/ES | 13 | E26 | 120 | 25,000 | 40° | 910 | 3500 | 80 | 1533 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1732404 | Y | PV-PAR38/13W/40/WFL40/D/ES | 13 | E26 | 120 | 25,000 | 40° | 910 | 4000 | 80 | 1533 | Y | Y | Y | 4.8 | 5.31 | 20 |
| 1732505 | Y | PV-PAR38/13W/50/WFL40/D/ES | 13 | E26 | 120 | 25,000 | 40° | 910 | 5000 | 80 | 1533 | Y | Y | Y | 4.8 | 5.31 | 20 |

¹ Enclosed Fixture Application



PV-PAR38, PV-PAR30LN, PV-PAR20

| Ordering Code | ES | Model Number | Watts | Base | Voltage (V) | Hour Rating | Beam Angle | Initial Lumens(lm) | CCT(K) | CRI | C.B.C.P. (cd) | EFA ¹ | Wet LOC. | Damp LOC. | M.O.D. (inch) | M.O.L. (inch) | Case QTY. | |
|---------------|----|---------------------------------|-------|------|-------------|-------------|------------|--------------------|--------|-----|---------------|------------------|----------|-----------|---------------|---------------|-----------|--|
| PV-PAR30 | | | | | | | | | | | | | | | | | | |
| 1732107 | Y | PV-PAR30LN/12W/27/WFL40/D/ES | 12 | E26 | 120 | 25,000 | 40° | 840 | 2700 | 80 | 1315 | Y | Y | Y | 3.74 | 4.84 | 20 | |
| 1732207 | Y | PV-PAR30LN/12W/30/WFL40/D/ES | 12 | E26 | 120 | 25,000 | 40° | 840 | 3000 | 80 | 1315 | Y | Y | Y | 3.74 | 4.84 | 20 | |
| 1732406 | Y | PV-PAR30LN/12W/40/WFL40/D/ES | 12 | E26 | 120 | 25,000 | 40° | 840 | 4000 | 80 | 1315 | Y | Y | Y | 3.74 | 4.84 | 20 | |
| 1732509 | Y | PV-PAR30LN/12W/50/WFL40/D/ES | 12 | E26 | 120 | 25,000 | 40° | 840 | 5000 | 80 | 1315 | Y | Y | Y | 3.74 | 4.84 | 20 | |
| 1762886 | Y | PV-PAR30LN/12W/30/WFL40/D/ES/BK | 12 | E26 | 120 | 25,000 | 40° | 840 | 3000 | 80 | 1315 | Y | Y | Y | 3.74 | 4.84 | 20 | |
| 1732206 | Y | PV-PAR30LN/12W/30/FL25/D/ES | 12 | E26 | 120 | 25,000 | 25° | 840 | 3000 | 80 | 2910 | Y | Y | Y | 3.74 | 4.84 | 20 | |
| 1732216 | Y | PV-PAR30/12W/30/WFL40/D/ES | 12 | E26 | 120 | 25,000 | 40° | 840 | 3000 | 80 | 1315 | Y | Y | Y | 3.74 | 3.63 | 20 | |
| PV-PAR20 | | | | | | | | | | | | | | | | | | |
| 1732109 | Y | PV-PAR20/7W/27/WFL40/D/ES | 7 | E26 | 120 | 25,000 | 40° | 500 | 2700 | 80 | 593 | Y | Y | Y | 2.47 | 3.46 | 50 | |
| 1732209 | Y | PV-PAR20/7W/30/WFL40/D/ES | 7 | E26 | 120 | 25,000 | 40° | 500 | 3000 | 80 | 593 | Y | Y | Y | 2.47 | 3.46 | 50 | |
| 1732408 | Y | PV-PAR20/7W/40/WFL40/D/ES | 7 | E26 | 120 | 25,000 | 40° | 500 | 4000 | 80 | 593 | Y | Y | Y | 2.47 | 3.46 | 50 | |
| 1732511 | Y | PV-PAR20/7W/50/WFL40/D/ES | 7 | E26 | 120 | 25,000 | 40° | 500 | 5000 | 80 | 593 | Y | Y | Y | 2.47 | 3.46 | 50 | |
| 1762887 | Y | PV-PAR20/7W/30/WFL40/D/ES/BK | 7 | E26 | 120 | 25,000 | 40° | 500 | 3000 | 80 | 593 | Y | Y | Y | 2.47 | 3.46 | 50 | |

Ordering Information Example: PV-PAR38/16W/27/WFL40/D/ES

| LED CLASS | LAMP TYPE | WATTAGE | CCT(K) | BEAM ANGLE | DIMMABLE | ENERGY STAR | Housing Colour |
|-----------|--|-------------------------|------------------------|---------------------------|----------|-------------|----------------------------|
| PV | PAR38 PAR30 PAR30LN (Long Neck) PAR20 | 16W 13W 12W 7W | 50, 40 35, 30 27 | WFL40 (40°) FL25 (25°) | D | ES | BK (Black) Blank(White) |