

LED LAMP

VIVID Series



LED T8 TUBE Ballast Bypass, Full Spectrum

Ideal for paint booth, printing workshop, art school or any other applications required ultimate light quality with energy saving solution.



Full Spectrum
R9 >90, CRI >95



3-year limited warranty

Operating temperature range -20 °C ~ +45 °C



Features & Benefits

Full spectrum (R9 >90), high CRI (95+), 5700K

PET film, shatterprotect¹

Double-ended installation

NSF/ANSI 2 certified²

50,000 hour life (L70), 180° Beam angle

120-347V, 48" length

Our safety features allow for installation as well as misapplication protection³

¹ Shatterprotect utilizes PET film to reduce the unexpected risk of shattering ² Contact your local Turolight representative for detail
³ Need to work with NSF certified lighting fixtures

Dimensional Drawing



Ordering Information Example: VIV-T8BPSP/195/18.5W/57/F/120-347V

Family Name	Lamp Type	Wattage	CCT	Frost	Voltage
VIV (Vivid)	T8BPSP/195 (Bypass, shatterprotect, double-ended, CRI≥95)	18.5W	57 (5700K)	F (Frost)	120-347V

Product Specification

Ordering Code	DLC	Model Number	Watts (W)	Voltage (V)	Initial Lumen (lm)	Base	Hour Rating	Beam Angle	CCT(K)	CRI	M.O.L. (inch)	Case QTY.
1753500	-	VIV-T8BPSP/195/18.5W/57/F/120-347V	18.5	120-347V	2100	G13	50,000	180°	5700	>95	48	10