LED FIXTURE

TL Series



Steel housing battery pack



1-year limited warranty

Operating temperature range $5^{\circ}C^{-}+35^{\circ}C$



TL-EMRM/275W





TL-EMRM/95W




TL-EMRM/34W

Features & Benefits

Steel housing, UL-94V-0 flame rating, fire-resistant Input Voltage: 120 / 347V With 2×5W 6500K heads 12V / 6V sealed lead-acid battery Damp location rated, IP Class: IP20, not intended for outdoor use Wall mounting, remote capable

Dimensional Drawing



Ordering Information Example: TL-EMRM/34W/6VDC/2-5W/120/347V

Family Name	Fixture Type	Wattage	Load Voltage	LED Heads	Input Voltage	
TL (Turolight)	EMRM (Emergency remote)	34W 95W 140W 275W	6VDC 12VDC	2-5W (With 2 \times 5W LED heads)	120/347V	

Product Specification

Ordering Code	Model Number	Description	Wattage (W)	Input Voltage (V)	LED Heads	Emergency Run Time (Min)	Mounting	Remote Capable	Damp Location	Dimensions L×W×H (inch)	Case QTY.
3466203	TL-EMRM/34W/6VDC/2-5W/120/347V	Metal Battery Pack (c/w 2x5W Heads) 34W, 6VDC, 120/347V	34	120/347V	2	30	Wall	Yes	Yes	11.81"×2.95"×9.72"	4
3466204	TL-EMRM/95W/12VDC/2-5W/120/347V	Metal Battery Pack (c/w 2x5W Heads) 95W, 12VDC, 120/347V	95	120/347V	2	30	Wall	Yes	Yes	12.20"×2.76"×10.63"	5
3466205	TL-EMRM/140W/12VDC/2-5W/120/347V	Metal Battery Pack (c/w 2x5W Heads) 140W, 12VDC, 120/347V	140	120/347V	2	30	Wall	Yes	Yes	13.50"×4.21"×12.52"	2
3466206	TL-EMRM/275W/12VDC/2-5W/120/347V	Metal Battery Pack (c/w 2x5W Heads) 275W, 12VDC, 120/347V	275	120/347V	2	30	Wall	Yes	Yes	15.28"×4.21"×13.70"	1



Email: sales@turolight.com Website: www.turolight.com

