

LED Mini Area Lighter



SSL-MAL	Segment	Wattage Range	Lumen Range
	Commercial & Industrial	Selectable Wattage	3,640-7,800lm

Features

- Autonomous dusk to dawn area lighter with superior Nema photo cell.
- Pressure Die Cast Aluminum Body with Operating temperature range of -40 ° C - +40 ° C.
- Field Selectable CCT (3000K, 4000K & 5000K) & Wattage (28W, 40W & 60W) along with Auto Sensing 120 – 347V Driver.
- Superior efficacy of ≥ 130 lm / W, Impact Resistant premium grade PC Lens designed for Type V light distribution.



Specifications

Housing:

Aluminum alloy pressure die casted housing & control gear box in grey finish for better heat dissipation and aesthetic appeal.

Optics:

Impact & UV Resistant PC Lens, precisely designed for Type V light distribution.

Mounting:

Suitable for wall mount and pole mount with optional mounting arm kit

Driver:

Auto Sensing 120 – 347V Driver with Operating temperature range of -40 ° C - +40 ° C

LED:


Field Selectable CCT of 3000K, 4000K & 5000K. Efficacy of ≥ 130 lm/w.

Controls:




Nema Photo Cell for Dusk to Dawn Auto Operation. Shorting Cap can be ordered separately, if Photo Cell is not required.



Polar Candela



Dimensional Drawing



Applications



Barn



Agricultural



Outbuildings

LED Mini Area Lighter



SSL-MAL	Segment	Wattage Range	Lumen Range
	Commercial & Industrial	Selectable Wattage	3,640-7,800lm

Ordering Information Example: SSL-MAL/60M/MW/MK/120-347V/PC/GR

Family Name	Fixture Type	Wattage	CCT (Kelvin)	Voltage	Diffuser	Finish	Accessories
SSL (Solid state lighting)	MAL (Mini area lighter)	60M/MW (Max. 60W, Selectable Wattage)	MK (Selectable Kelvin/ CCT)	120-347V	PC (Polycarbonate)	GR (Grey)	SSL-MAL/90D/ARM

Product Information

Ordering Code	DLC Premium	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Wet Location	Case QTY.
3680321	Y	SSL-MAL/60M/MW/MK/120-347V/PC/GR	60-40-28	120-347	50,000	7800-5200-3640	30-40-50	≥70	Yes	1
3660206	-	SSL-MAL/90D/ARM	90 Degree mounting arm c/w bracket							

Accessories

SSL-MAL/90D/ARM



Related Products



DL-VT2



Wall Packs



Jam Jar



Security Light