

LED LAMP

ARTISAN Series



LED G16.5, G30, G40

Low Flicker



2-year limited warranty

Operating temperature range -20° C ~ +40° C



Features & Benefits


- Reduced flicker down to 10%
 - Compare to 6.6% traditional incandescent
 - Far below California T20 standard 30%
 - Significantly improve light quality
 - Optimize eye comfort

With clear, amber or milky white glass cover

15,000 hour life (L70), high CRI (80+), dimmable,

Damp location rated

Dimensional Drawing



Ordering Information Example: AR-G16.5LF/4W/27/E12/D/C

| Family Name | Lamp Type | Wattage | CCT | Base | Dimmable | Cover |
|--------------|------------------------------|---------|------------|-------------|--------------|------------------|
| AR (Artisan) | G16.5LF (G16.5, Low flicker) | 4W | 22 (2200K) | E12 | D (Dimmable) | C (Clear) |
| | G30LF (G30, Low flicker) | 5W | 27 (2700K) | Blank (E26) | | A (Amber) |
| | G40LF (G40, Low flicker) | | 30 (3000K) | | | MW (Milky white) |
| | G16.5, G40 | | | | | |

Product Specification

| Ordering Code | Model Number | Watts (W) | Replacement Filament | Replacement Incandescent | Base | Voltage (V) | Hour Rating | Beam Angle | Initial Lumens (lm) | CCT(K) | CRI | Damp LOC. | M.O.L. (inch) | Case QTY. |
|---------------|---------------------------|-----------|----------------------|--------------------------|------|-------------|-------------|------------|---------------------|--------|-----|-----------|---------------|-----------|
| 1771146 | AR-G16.5LF/4W/27/E12/D/C | 4 | - | 40W | E12 | 120 | 15,000 | 330° | 350 | 2700 | 80 | Y | 3.31 | 50 |
| 1771208 | AR-G16.5LF/4W/30/E12/D/C | 4 | - | 40W | E12 | 120 | 15,000 | 330° | 350 | 3000 | 80 | Y | 3.31 | 50 |
| 1771212 | AR-G16.5LF/4W/30/E12/D/MW | 4 | - | 40W | E12 | 120 | 15,000 | 330° | 300 | 3000 | 80 | Y | 3.31 | 50 |
| 1771151 | AR-G16.5LF/5W/27/E12/D/C | 5 | - | 50W | E12 | 120 | 15,000 | 330° | 500 | 2700 | 80 | Y | 3.31 | 50 |
| 1771109 | AR-G16.5/4W/27/D/C** | 4 | - | 40W | E26 | 120 | 15,000 | 330° | 350 | 2700 | 80 | Y | 3.31 | 50 |
| 1771147 | AR-G30LF/5W/27/D/C | 5 | - | 50W | E26 | 120 | 15,000 | 330° | 500 | 2700 | 80 | Y | 5.28 | 40 |
| 1771215 | AR-G30LF/5W/30/D/C | 5 | - | 50W | E26 | 120 | 15,000 | 330° | 500 | 3000 | 80 | Y | 5.28 | 40 |
| 1771230 | AR-G30LF/5W/30/D/C/ES | 5 | - | 50W | E26 | 120 | 15,000 | 330° | 500 | 3000 | 80 | Y | 5.28 | 40 |
| 1771216 | AR-G30LF/5W/30/D/MW | 5 | - | 50W | E26 | 120 | 15,000 | 330° | 450 | 3000 | 80 | Y | 5.28 | 40 |
| 1771929 | AR-G30LF/5W/22/D/A | 5 | 50W | - | E26 | 120 | 15,000 | 330° | 450 | 2200 | 80 | Y | 5.28 | 40 |
| 1771217 | AR-G40LF/4W/30/D/C | 4 | - | 40W | E26 | 120 | 15,000 | 330° | 350 | 3000 | 80 | Y | 6.77 | 8 |
| 1772910 | AR-G40LF/5W/22/D/A | 5 | 50W | - | E26 | 120 | 15,000 | 330° | 500 | 2200 | 80 | Y | 6.77 | 8 |
| 1771218 | AR-G40LF/4W/30/D/MW | 4 | - | 40W | E26 | 120 | 15,000 | 330° | 320 | 3000 | 80 | Y | 6.77 | 8 |
| 1771909 | AR-G40/5W/22/D/A** | 5 | 40W | - | E26 | 120 | 15,000 | 330° | 400 | 2200 | 80 | Y | 6.77 | 8 |

** AR-G16.5, AR-G40 are not the low flicker items