

LED Vapor Tight



DL-VT3	Segment	Wattage Range	Lumen Range
	Commercial & Industrial	Selectable Wattage (24W-48W)	3,285-6,750lm

Features

- Unibody Polycarbonate Back housing with Gasket. White powder coated CRCA LED Tray for better Thermal Management.
- IP 66 Wet Location rated with operating temperature range of -40 °C - +35 °C.
- Field Selectable CCT (3500K, 4000K & 5000K) along with 120-347V LED Auto-Sensing driver.
- NEMA 4X and NSF Certified Field Selectable Multiple Wattage.



Specifications

Housing:

Polycarbonate Back Housing + Gasket with CRCA LED Tray for better heat dissipation.

Optics:

UV-stabilized and high-impact-resistant (IK10) Polycarbonate lens with prismatic design low glare and 304 stainless steel latches.

Mounting:

Surface & Suspended Mounting options via supplied clamps.

Driver:


120-347V LED Auto-Sensing driver with Operating temperature range of -40 °C ~ +35 °C.

LED:


Field Selectable CCT of 3500K, 4000K & 5000K. Efficacy of $\geq 135\text{lm/w}$.

Controls:

Haisen LV6S Low Voltage Sensor with 0-10V Dimming.



Dimensional Drawing



	L	W	H
4FT	48"	3.9"	3.3"

Applications



Warehouses



Factory



Multilevel Car Park



Metro Stations

LED Vapor Tight



DL-VT3	Segment	Wattage Range	Lumen Range
	Commercial & Industrial	Selectable Wattage (24W-48W)	3,285-6,750lm

Ordering Information Example: DL-VT3/4FL/MW/MK/120-347V/D/LV6S

Family Name	Fixture Type	Size	Wattage	CCT	Voltage	Dimmable	Accessories
DL (Deltalum)	VT3 (Vapor tight)	4F (4')	MW (Selectable Wattage)	MK (Selectable Kelvin)	120-347V	D (0-10V dimming)	LV6S (Low voltage microwave sensor, factory installed)

Product Information

Ordering Code	DLC Premium	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Beam Angle	Initial Delivered Lumens (lumen)	CCT (K)	CRI	M.O.L (inch)	Case QTY.
3682234	Yes	DL-VT3/4FS/MW/MK/120-347V/D	36-31-24	120-347V	50,000	100°	4500-4050-3285	35-40-50	>80	48	8
3682235	Yes	DL-VT3/4FL/MW/MK/120-347V/D	48-41-33	120-347V	50,000	100°	6750-5310-4365	35-40-50	>80	48	8
3682236	Yes	DL-VT3/4FS/MW/MK/120-347V/D/LV6S	36-31-24	120-347V	50,000	100°	4500-4050-3285	35-40-50	>80	48	8
3682237	Yes	DL-VT3/4FL/MW/MK/120-347V/D/LV6S	48-41-33	120-347V	50,000	100°	6750-5310-4365	35-40-50	>80	48	8
3660196	-	DL-EC/LV6S/CONTROLLER	Remote controller for LV6S sensor								

Accessories

LV6S low voltage sensor



Operating voltage	10.5-15V DC (supply current >50mA, operating current <30mA)
Output	DIM/1-10V
Stand-by Power	<0.5W
Detection area	100%/75%/50%/25%
Hold-time	5s/30s/1min/3 min/5min/10min/20min/30min
Daylight threshold	2lux/10lux/30lux/50lux/80lux/120lux/Disable
Stand-by period	0s/10s/30s/min/5min/10min/30min/+∞
Stand-by dimming level	10%/20%/30%/50%
Mounting height	Max.6m (ceiling mounted)
Detection range	Radius:2-5m(ceiling mounted)
Detection angle	360°(ceiling mounted); <150° (Wall Mounted)
Operating temperature	-40°C~+80°C
Warranty	5 years

Note:
Different applications and places will make different detection distance, our result is just for your information. Motion sensor setting and dimming setting please refer to remote control HD05R Lo/Vo controller Haisen.

DL-EC/LV6S/CONTROLLER



- Microwave can penetrate walls or glass thinner than 20cm, movement in adjacent corridors may be detected.
- Detection area will be affected by speed of motion, mounting height and movement volume.
- Installation shall not be mounted to avoid false trigger caused by the luminaire itself shaking. (Rooftop HVAC, upper floor vibration, etc.)
- Shall not be installed next to large operating machines such as ventilator/ceiling fan to avoid false triggering caused by machine vibration.
- They cannot penetrate metal. Large metal object near the sensor may create a "dead zone" behind it.
- Microwave sensors have advantage over PIR device in that they can operate in hot environments, however, they are sensitive devices and can be prone to false detection by everyday items like ceiling fans, moving branches or curtains, loose packaging, etc.

Other options may be available, consult Turolight Sales. Specifications and data are subject to change without notice.

Related Products



SSL-CHB2



SSL-LHB5



DL-EC2