

ZENITH 60 Linear Pendant Direct/Indirect Luminaire


ZNTH60-PDI combines both direct and indirect lighting element in a sleek and contemporary pendant design. Selectable wattage and selectable CCT (Correlated Color Temperature) options offer enhanced flexibility. Individual units are easily combined into row mounting with supplied joiner kits.

Specifications

- Housing :** The Zenith60 housing is constructed of extruded aluminum 6063T5.
- End Caps:** Die cast aluminum fastened to housing with internal fasteners.
- Optics:** Frosted polycarbonate snap in lens with Lambertian distribution.
- Driver :** LED drivers for both Direct and Indirect outputs are contractor wattage selectable and universal 120-347V input (up to 3 different outputs – see output chart). They can be adjusted independently of each other allowing maximum flexibility. Less than 20% THD and 0-10V dimmable down to 1%.
- Power Feed:** The unit comes complete with 18/5 STW 600V rated power cable (White or Black) preinstalled with internal quick connect. For row mounting the power feed is easily removed where not needed.
- Suspension:** Galvanized 1.5mm (1/16") aircraft cable with fully adjustable grippers for ease of on-site leveling. All suspension points are field adjustable along the length of a unit.
- LED:** Name brand LED with long life offered in standard 80+ CRI. On board selectable CCT offers maximum flexibility (3000K/3500K/4000K).
- Finish:** Polyester powder painted finish



Dimensional Drawing



| | L | W | H |
|-----------------------|--------|-------|-------|
| 4FT | 47.24" | 2.36" | 3.35" |
| 8FT | 94.49" | 2.36" | 3.35" |
| 6FT (optional) | 70.86" | 2.36" | 3.35" |

Ordering Information Example: ZNTH60-PDI/4/F/F/10L/MK3/80/UN3/D1/B/B6/S6/B

| Family/ Series | Mounting | Function | Length | Diffuser Direct | Diffuser Indirect | Max Total Lumens | CCT 30K/35K/40K | CRI | Voltage | Driver | Housing Finish | Cord Colour/Length | Suspension Length | Canopy Colour | Options* |
|----------------|-----------|---------------------------------|--------|-----------------|-------------------|------------------|-----------------|-----|--------------|-----------------|----------------|--------------------|-------------------|---------------|--------------------|
| ZNTH60 | P Pendant | DI Direct/ Indirect C Custom | 4 4ft | F Frosted | F Frosted | 10L 10000 (4ft) | MK3 | 80 | UN3 120-347V | D1 0-10V Dim 1% | W White | W6 White 6ft | S6 6ft | W White | K1 White Cable kit |
| | | | 8 8ft | | | 20L 20000 (8ft) | | | | | B Black | B6 Black 6ft | | B Black | K2 Black Cable kit |
| | | | | | | | | | | | C Custom | | | | C Custom |

* K1: 10Ft., Suspension, Power Cable White & 2 Aircraft Cable Kit
 K2: 10Ft., Suspension, Power Cable Black & 2 Aircraft Cable Kit

Light Outputs Function: Direct / Indirect

| Catalogue Code | Voltage | Dimension | | | | Efficacy lm/W | CRI | Direct | | | UP Light | | |
|-----------------------------|----------|-----------|-------|-------|-------------|------------------|-----|--------|---------------------|--------------------|----------|---------------------|--------------------|
| | | L | W | H | CCT | | | Watts | Delivered Lumens | Lumens per foot | Watts | Delivered Lumens | Lumens per foot |
| ZNTH60-PDI/4 | 120-347V | 47.24" | 2.36" | 3.35" | 30K/35K/40K | 130 | 80+ | 40 | 5200 | 1300 | 33 | 4290 | 1073 |
| | | | | | | | | 33 | 4290 | 1073 | 28 | 3640 | 910 |
| | | | | | | | | 25 | 3250 | 813 | 22 | 2860 | 715 |
| ZNTH60-PDI/8 | 120-347V | 94.49" | 2.36" | 3.35" | 30K/35K/40K | 130 | 80+ | 80 | 10400 | 1300 | 66 | 8580 | 1073 |
| | | | | | | | | 66 | 8580 | 1073 | 56 | 7280 | 910 |
| | | | | | | | | 50 | 6500 | 813 | 44 | 5720 | 715 |
| ZNTH60-PDI/C (6ft optional) | 120-347V | 70.86" | 2.36" | 3.35" | 30K/35K/40K | 130 | 80+ | 62 | 8060 | 1008 | 54 | 7020 | 878 |
| | | | | | | | | 54 | 7020 | 878 | 46 | 5980 | 748 |
| | | | | | | | | 46 | 5980 | 748 | 39 | 5070 | 634 |