

Project:			
Ordering info:			
Submitted by:		Date:	



Linear Pendant Luminaire ZNTH60-PD (Direct) ZNTH60-PDI (Direct/Indirect)	PD	Wattage Range 24-79W	Lumen Range 3,262-11,000lm	Efficacy 138lm/W	Light Performance 816-1,375lm/ft													
	PDI	Wattage Range ↓25-79W ↑21-70W	Lumen Range ↓3,380-10,869lm ↑2,839-9,631lm	Efficacy 136lm/W	Light Performance ↓826-1,359lm/ft ↑710-1,204lm/ft													
	3CCT Selectagle 3000K 3500K 4000K																	
	Finishes Black White																	
		<table border="1"> <thead> <tr> <th></th> <th>L</th> <th>W</th> <th>H</th> </tr> </thead> <tbody> <tr> <td>4FT</td> <td>1200mm 47.24"</td> <td>60mm 2.36"</td> <td>85mm 3.35"</td> </tr> <tr> <td>8FT</td> <td>2390mm 94.09"</td> <td>60mm 2.36"</td> <td>85mm 3.35"</td> </tr> </tbody> </table>				L	W	H	4FT	1200mm 47.24"	60mm 2.36"	85mm 3.35"	8FT	2390mm 94.09"	60mm 2.36"	85mm 3.35"		
	L	W	H															
4FT	1200mm 47.24"	60mm 2.36"	85mm 3.35"															
8FT	2390mm 94.09"	60mm 2.36"	85mm 3.35"															

Ordering Guide Example: ZNTH60-PD/4/F/05L/MK3/80/UN3/D1/B/B6/S6/B

Family/Series	Mounting	Function	Length	Diffuser Direct	Diffuser Indirect	Max Total Lumens	CCT	CRI	Voltage	Driver	Housing Finish	
ZNTH60	P	Pendant	D	Direct	-	05L 5000 (4ft)	MK3	80	UN3	120-347V	D1 0-10V Dim 1%	W White
						10L 10000 (8ft)						B Black
			4ft	F Frosted	F Frosted	10L 10000 (4ft)						C Custom
						8ft						20L 20000 (8ft)

Cord Colour/Length	Suspension Length	Canopy Colour
W6 White 6ft	S6 6ft	W White
B6 Black 6ft		B Black
		C Custom

Light Outputs

Catalogue Code	Voltage	Dimension			CCT	Efficacy lm/W	CRI	Direct			UP Light		
		L	W	H				Watts	Delivered Lumens	Lumens per foot	Watts	Delivered Lumens	Lumens per foot
ZNTH60-PD/4	120-347V	47.24"	2.36"	3.35"	30K-35K-40K	130	80+	39	5300	1325	-		
								32	4349	1087	-		
								24	3262	816	-		
ZNTH60-PD/8	120-347V	94.09"	2.36"	3.35"	30K-35K-40K	130	80+	79	11000	1375	-		
								63	8772	1097	-		
								48	6684	836	-		
ZNTH60-PDI/4	120-347V	47.24"	2.36"	3.35"	30K-35K-40K	130	80+	39	5273	1318	32	4327	1082
								32	4327	1082	26	3515	879
								25	3380	845	21	2839	710
ZNTH60-PDI/8	120-347V	94.09"	2.36"	3.35"	30K-35K-40K	130	80+	79	10869	1359	70	9631	1204
								63	8668	1084	58	7980	998
								48	6604	826	46	6329	791

Project:	
Ordering info:	
Submitted by:	Date:



Specifications

Housing:	The Zenith60 housing is constructed of extruded aluminum 6063T5.	Power Feed:	The unit comes complete with 18/5 STW 600V rated power cable (White or Black) preinstalled with internal quick connect. For row mounting the power feed is easily removed where not needed.
End Caps:	Die cast aluminum fastened to housing with internal fasteners.	Suspension:	Galvanized 1.5mm (1/16") aircraft cable with fully adjustable grippers for ease of on-site leveling. All suspension points are field adjustable along the length of a unit.
Optics:	Frosted polycarbonate snap in lens with Lambertian distribution.	LED:	Name brand LED with long life offered in standard 80+ CRI. On board selectable CCT offers maximum flexibility (3000K/3500K/4000K).
Driver:	LED drivers are contractor wattage selectable and universal 120-347V input (up to 3 different outputs – see output chart). Less than 20%THD and 0-10V dimmable down to 1%. The drivers of the Direct/Indirect units can be adjusted independently of each other allowing maximum flexibility.	Finish:	Polyester powder painted finish

Model & Ordering Information

Ordering Code	Model Number	Description	Case QTY
3695002	ZNTH60-PD/4/F/05L/MK3/80/UN3/D1/B/B6/S6/B	4Ft., Direct, Selectable 40-33-25W, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, Black Finish.	4
3695001	ZNTH60-PD/4/F/05L/MK3/80/UN3/D1/W/W6/S6/W	4Ft., Direct, Selectable 40-33-25W, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, White Finish.	4
3696002	ZNTH60-PD/8/F/10L/MK3/80/UN3/D1/B/B6/S6/B	8Ft., Direct, Selectable 80-66-50W, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, Black Finish.	2
3696001	ZNTH60-PD/8/F/10L/MK3/80/UN3/D1/W/W6/S6/W	8Ft., Direct, Selectable 80-66-50W, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, White Finish.	2
3695004	ZNTH60-PDI/4/F/F/10L/MK3/80/UN3/D1/B/B6/S6/B	4Ft., Direct/Indirect, Selectable 40-33-25W Down, 33-28-22W Up, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, Black Finish.	4
3695003	ZNTH60-PDI/4/F/F/10L/MK3/80/UN3/D1/W/W6/S6/W	4Ft., Direct/Indirect, Selectable 40-33-25W Down, 33-28-22W Up, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, White Finish.	4
3696004	ZNTH60-PDI/8/F/F/20L/MK3/80/UN3/D1/B/B6/S6/B	8Ft., Direct/Indirect, Selectable 80-66-50W Down, 66-56-44W Up, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, Black Finish.	2
3696003	ZNTH60-PDI/8/F/F/20L/MK3/80/UN3/D1/W/W6/S6/W	8Ft., Direct/Indirect, Selectable 80-66-50W Down, 66-56-44W Up, Selectable 30-35-40K, 120-347V, 0-10V Dim 1%, c/w 6' Pwr. & Susp. cables, White Finish.	2
3690001	ZNTH60-K1	10Ft., Suspension, Power Cable White & 2 Aircraft Cable Kit.	-
3690002	ZNTH60-K2	10Ft., Suspension, Power Cable Black & 2 Aircraft Cable Kit.	-
3690004	ZNTH60-K4	Joiner Kit, for Row mounting.	-

Mounting

