

ZNTH60-PRO/PD

ZENITH 60 PRO Linear Pendant Direct Luminaire

ZNTH60-PRO provides a direct lighting element in a sleek and contemporary pendant design. Selectable wattage and selectable CCT (Correlated Color Temperature) options offer enhanced flexibility.



Specifications

Housing: The Zenith60 housing is constructed of extruded aluminum

6063T5.

End Caps: Die cast aluminum fastened to housing with internal fasteners.

Optics: Frosted polycarbonate snap in lens with Lambertian distribution.

Driver: LED drivers for Direct outputs are contractor wattage selectable and universal 120-347V input (up to 3 different outputs

- see output chart). Less than 20%THD and 0-10V dimmable

down to 1%.

Power Feed: The unit comes complete with 18/5 STW 600V rated power ca-

ble (White).

Suspension: Galvanized 1.5mm (1/16") aircraft cable with fully adjustable

grippers for ease of on-site leveling. All suspension points are

field adjustable along the length of a unit.

LED: Name brand LED with long life offered in standard 80+

CRI. On board selectable CCT offers maximum flexibility

(3000K/3500K/4000K).

Finish: Polyester powder painted finish


















Dimensional Drawing





	L	W	Н
4FT	47.24"	2.36"	3.35"

Ordering Information Example: ZNTH60-PRO/PD/4/F/05L/MK3/80/UN3/D1/W/W6/S6/W

Family/ Series	Mountin	F	unction	Leng	h		iffuser MaxTotal CCT irect Lumens 30K/35K/4			CRI Voltage						Cord Colour/Length						Options*			
ZNTH60-PR	0 P Pend	ant D	Direct	4	4ft	F	Frosted	05L	5000 (4ft)	MK3	80	UN3	120-347V	D1	0-10V Dim 1%	W	White	W6	White 6ft	S6	6ft	W	White	K1	White Cable kit

^{*} K1: 10Ft., Suspension, Power Cable White & 2 Aircraft Cable Kit

Light Outputs Function: Direct

Ordorina				Dimensi	on		Efficacy		Direct				
Ordering Code	Model Number	Voltage	L	W	Н	ССТ	lm/W	CRI	Watts	Delivered Lumens	Lumens per foot		
3695005	ZNTH60-PR0/PD/4/F/05L/MK3/80/UN3/D1/W/W6/S6/W	120-347V	47.24"	2.36"	3.35"	30K/35K/40K	130	80+	40	5200	1300		
									33	4290	1073		
									25	3250	813		